

LEATHER BAG



Flores
Patterns

Dimensions:

Bag Size: 321 x 252 x 117 mm / 12.63x 9.92 x 4.6 inch

Materials:

- 01 Adjuster Slide Buckle: inner 36mm/ 1.42inch (Position Strap)
- 02 Adjuster Slide Buckle: inner 27mm/ 1.06inch (Position G7)
- 02 Rectangle Buckle Ring: inner 36mm/ 1.42inch (Position G10)
- 02 Magnetic Snap: 12mm/ 0.47inch (Position G4 and G9)
- 01 Zipper: 220 mm/ 8.66 inch (Position Zipper 1)
- 01 Zipper: 290 mm/ 11.41 inch (Position Zipper 2)
- The inner lining fabric has the same size as the pattern
- Use leather with a thickness of 2 - 2.5mm / 0.079 - 0.098 inch
- Strap: 1200x 36 mm/ 47.24 x 1.42 inch

Notes:

- Print the pattern in A1 or A4 size at 100% scale
- If using A4 size, combine the pieces into a pattern like A1 size
- Look at the image for more details on the positions G1 to G13
- Sew G5 to G1, and sew G5 to G4
- Attach the Magnetic Snap to pieces G4
- Sew G6 to G3, Zipper 1 at the same time
- Sew G4 to G1
- Sew G1, G2, G3
- Sew G7 to G6
- Sew G8 and G9 as shown in the picture, and attach the magnet to G9
- Attach Rectangle Buckle Ring to G10 and sew G10 to G2
- Sew G13 to G1 and G3, Zipper 2 at the same time
- Sew G11 to position Zipper 1 and Zipper 2, sew G12 to Zipper 2
- Connect the S part of the strap



20mm

1 inch

Instructions:

1. Preparing the Pattern:

Print the pattern on A1 or A4 paper at 100% scale. If printing on A4 sheets, you'll need to combine the sheets into a single A1 size sheet.

Cut the leather and lining pieces according to the pattern. Label each piece for easier assembly.

2. Assembling the Front and Back Panels:

Sew G5 to G1:

Position G5 (bottom panel) along the bottom edge of G1 (front panel) and sew them together. Use a sewing machine designed for leather or hand-stitch using waxed thread. Reinforce the corners where G5 and G1 meet, making sure the leather doesn't pucker.

Sew G5 to G4:

Attach G5 to G4 (the back panel) in a similar fashion. Ensure the seams are consistent with the front.

3. Attaching the Magnetic Snap:

Sew Magnetic Snap on G4 and G9:

Before sewing the panels together, insert and sew the magnetic snap onto G4 (front flap) and G9 (strap). Ensure it is aligned with the corresponding snap placement on the front flap of G4.

4. Zipper 1 and Zipper 2 Installation:

Sew Zipper 1 onto G6:

Attach Zipper 1 to G6 (pocket panel) before assembling the bag further. Pin or clip the zipper to G6 so it is centered and aligned.

Use a zipper foot on your sewing machine to stitch along both sides of the zipper.

Install Zipper 2 to G11 and G13:

Pin Zipper 2 to G11 and G13, making sure it opens and closes smoothly before sewing. Stitch the zipper into place, ensuring that it's flush with the leather and doesn't catch.

5. Assembling the Front Flap:

Sew G6 to G3 (back panel) along with Zipper 1:

After attaching Zipper 1 to G6, align and sew G6 to G3. This creates the back panel of the bag with a functional zippered compartment.

Stitch G4 to G1:

Align the top edge of G4 (front flap) with G1 (front panel) and sew them together.

Make sure the flap folds over neatly when finished, and that the magnetic snap connects properly.

6. Preparing the Strap:

Sew G7 to G6 (Strap Attachment):

Attach G7 (strap tabs) to the side of the bag, reinforcing the stitching, as these will bear the weight of the bag when carried.

Attach the Adjuster Slide Buckle to G7 and sew it securely.

7. Assembling the Sides and Bottom:

Sew the side pieces (G2) to G1 and G3:

Align G2 with G1 and G3, sewing down both sides. Ensure that the side pieces are properly aligned with the front and back panels for a clean finish.

Attach G5 (bottom piece) to the side pieces:

After sewing the sides, attach the bottom (G5) to G2 (the side panels). Make sure that all corners are even, and reinforce the stitching at stress points, such as the corners.

8. Securing Hardware and Finishing:

Attach Magnetic Snap on G8 and G9 (straps):

Before sewing the straps to the bag, insert the magnetic snaps onto G8 and G9 as per the pattern markings. This allows the front flap to close securely.

Attach Rectangle Buckle Rings on G10:

Sew the Rectangle Buckle Rings onto G10, which is part of the strap system. Attach G10 to G2 (side panel) securely.

Attach Zipper 2 and G11 to G13:

Once Zipper 2 is attached, sew G11 (pocket flap) to G13, ensuring the pocket and zipper work smoothly.

Reinforce all stitching where hardware and zippers are installed to ensure durability.

9. Final Adjustments:

Connect S-Part of Strap:

Finish assembling the strap by attaching the S part (adjustable strap section) to the adjuster buckle. Secure all the strap ends using rivets or strong stitching.



Flores
Patterns